

# **AGREEMENT**

## **CONCERNING THE ADOPTION OF UNIFORM CONDITIONS OF APPROVAL AND RECIPROCAL RECOGNITION OF APPROVAL FOR MOTOR VEHICLE EQUIPMENT AND PARTS**

**done at Geneva on 20 March 1958**

Addendum 30: Regulation No. 31

Revision 1

**Incorporating:**

**01 series of amendments — Date of entry into force: 7 February 1983**

**02 series of amendments — Date of entry into force: 30 March 1988**

**Supplement 1 to the 02 series of amendments — Date of entry into force: 28 February 1990**

**Supplement 2 to the 02 series of amendments — Date of entry into force: 27 October 1992**

**UNIFORM PROVISIONS CONCERNING THE APPROVAL  
OF HALOGEN SEALED-BEAM UNIT (HSB UNIT) MOTOR VEHICLE HEADLAMPS  
EMITTING AN ASYMMETRICAL PASSING BEAM OR A DRIVING BEAM OR BOTH**



**UNITED NATIONS**



Regulation No. 31

UNIFORM PROVISIONS CONCERNING THE APPROVAL OF HALOGEN SEALED-BEAM UNIT  
(HSB UNIT) MOTOR VEHICLE HEADLAMPS EMITTING AN ASYMMETRICAL PASSING  
BEAM OR A DRIVING BEAM OR BOTH

CONTENTS

	<u>Pages</u>
REGULATION	
1. Scope . . . . .	5
2. Definitions . . . . .	5
3. Application for approval . . . . .	6
4. Markings . . . . .	7
5. Approval . . . . .	7
6. General specifications . . . . .	11
7. Rated and test values . . . . .	12
8. Illumination . . . . .	12
9. Colour . . . . .	15
10. Gauging of discomfort . . . . .	16
11. Conformity of production . . . . .	16
12. Penalties for non-conformity of production . . . . .	16
13. Modification and extension of approval of a type of halogen sealed-beam headlamp unit (HSB unit) . . . . .	16
14. Production definitely discontinued . . . . .	17
15. Transitional provisions . . . . .	17
16. Names and addresses of technical services responsible for conducting approval tests and of administrative departments . . . . .	18

CONTENTS (continued)

ANNEXES

- Annex 1 - Communication concerning the approval or extension or refusal or withdrawal of approval or production definitely discontinued of a type of halogen sealed-beam headlamp unit (HSB unit) pursuant to Regulation No. 31
- Annex 2 - Example of arrangements of approval marks
- Annex 3 - Electrical connections of HSB units
- Annex 4 - Measuring screen
- Annex 5 - Verification of conformity of production of HSB units
- Annex 6 - Tests for stability of photometric performance of headlamps in operation
- Annex 7: Requirements for lamps incorporating lenses of plastic material - testing of lens or material samples and of complete lamps.
-

Regulation No. 31

UNIFORM PROVISIONS CONCERNING THE APPROVAL OF HALOGEN SEALED-BEAM UNIT  
(HSB UNIT) MOTOR VEHICLE HEADLAMPS EMITTING AN ASYMMETRICAL PASSING  
BEAM OR A DRIVING BEAM OR BOTH

1. SCOPE 1/

This Regulation applies to motor vehicle headlamps which may incorporate lenses of glass or plastic material.

2. DEFINITIONS

For the purpose of this Regulation,

- 2.1. "Halogen sealed-beam headlamp unit" (hereinafter termed "HSB unit") means a headlamp whose components, including a reflector of glass, metal or other material, an optical system and one or more halogen light sources, form an integral whole which is indivisibly joined and cannot be dismantled without rendering the unit completely unusable. Such units are:
- 2.1.1. of "category 1", when they emit only a driving beam;
- 2.1.2. of "category 21", when they emit only a passing beam;
- 2.1.3. of "category 22", when they emit, at the user's choice, either a driving beam or a passing beam;
- 2.2. "Lens" means the outermost component of the headlamp (unit) which transmits light through the illuminating surface;
- 2.3. "Coating" means any product or products applied in one or more layers to the outer face of a lens;
- 2.4. "HSB units of different types" means units which differ in such essential respects as:
- 2.4.1. the trade name or mark;
- 2.4.2. the characteristics of the optical system;
- 2.4.3. the inclusion or elimination of components capable of altering the optical effects by reflection, refraction, absorption and/or deformation during operation; the fitting or elimination of filters intended solely to change the colour of the beam but not its light distribution does not constitute a change of type;

---

1/ Nothing in this Regulation shall prevent a Party to the Agreement applying this Regulation from prohibiting the combination of an HSB unit incorporating a lens of plastic material approved under this Regulation with a mechanical headlamp-cleaning device (with wipers).

- 2.4.4. the rated voltage;
- 2.4.5. the shape of the filament or filaments;
- 2.4.6. the kind of beam produced (passing beam, driving beam or both);
- 2.4.7. the materials constituting the lens and coating, if any.

### 3. APPLICATION FOR APPROVAL

3.1. The application for approval shall be submitted by the owner of the trade name or mark or by his duly accredited representative. It shall specify:

3.1.1. whether the HSB unit is intended to provide both a passing beam and a driving beam or only one of these beams;

3.1.2. where the HSB unit is intended to provide a passing beam, whether it is designed for both right-hand and left-hand traffic or for right-hand or left-hand traffic only.

3.2. Every application for approval shall be accompanied by:

3.2.1. drawings in triplicate, sufficiently detailed to permit identification of the type and giving a front view of the HSB unit (with, if applicable, details of the lens moulding) and a cross-section; also the filament(s) and shield(s) shall be shown on the drawings at a scale of 2:1 both in front view and in side view; the drawing must show the position intended for the approval number and the additional symbols in relation to the circle of the approval mark;

3.2.2. a brief technical description;

3.2.3. samples as follows:

3.2.3.1. for approval of an HSB unit emitting uncoloured light: five samples,

3.2.3.2. for approval of an HSB unit emitting coloured light: two coloured-light samples and five uncoloured-light samples of the same type, differing from the type submitted, only in that the lens or filter is not coloured,

3.2.3.3. in the case of HSB units which emit coloured light, which differ from uncoloured-light units only in the colour of light emitted and which have already satisfied the requirements of paragraphs 6., 7. and 8. below, it will be sufficient to submit only one sample of a coloured-light unit to undergo the tests described in paragraph 9. below.

- 3.2.4. For the test of plastic material of which the lenses are made:
- 3.2.4.1. thirteen lenses.
- 3.2.4.1.1. Six of these lenses may be replaced by six samples of material at least 60 x 80 mm in size, having a flat or convex outer surface and a substantially flat area (radius of curvature not less than 300 mm) in the middle measuring at least 15 x 15 mm.
- 3.2.4.1.2. Every such lens or sample of material shall be produced by the method to be used in mass production,
- 3.2.4.2. a reflector to which the lenses can be fitted in accordance with the manufacturer's instructions.
- 3.3. The characteristics of the materials making up the lenses and coatings, if any, should be accompanied by the test report on these materials and coatings if they have already been tested.
- 3.4. The competent authority shall verify the existence of satisfactory arrangements for ensuring effective control of the conformity of production before type approval is granted.
4. MARKINGS 2/
- 4.1. HSB units submitted for approval shall bear the trade name or mark of the applicant.
- 4.2. They shall comprise, on the lens, a space of sufficient size to accommodate the approval mark and the additional symbols provided for in paragraph 5. below; the space shall be shown in the drawings referred to in paragraph 3.2.1. above.
- 4.3. They shall bear, either on the lens or on the body, the rated voltage and rated wattage of the driving-beam filament, followed by the rated wattage of the passing-beam filament, where applicable.
5. APPROVAL
- 5.1. General
- 5.1.1. If all the HSB unit type samples submitted in pursuance of paragraph 3. above meet the requirements of this Regulation, approval shall be granted.

---

2/ In the case of units designed to meet the requirements of traffic moving on one side of the road only (either right or left), it is further recommended that the area which can be occulted to prevent discomfort to users in a country where traffic moves on the side of the road opposite to that for which the unit was designed should be outlined indelibly on the lens. This marking is not necessary, however, where the area is clearly apparent from the design.

- 5.1.2. Where grouped, combined or reciprocally incorporated lamps satisfy the requirements of more than one Regulation, a single international approval mark may be affixed provided that each of the grouped, combined or reciprocally incorporated lamps satisfies the provisions applicable to it.
- 5.1.3. An approval number shall be assigned to each type approved. Its first two digits (at present 02) shall indicate the series of amendments incorporating the most recent major technical amendments made to the Regulation at the time of issue of the approval. The same Contracting Party may not assign the same number to another type of HSB unit covered by this Regulation except in the case of an extension of the approval to a device differing only in the colour of the light emitted.
- 5.1.4. Notice of approval or of extension or refusal or withdrawal of approval or production definitely discontinued of a type of optical unit pursuant to this Regulation shall be communicated to the Parties to the 1958 Agreement applying this Regulation, by means of a form conforming to the model in annex 1 to this Regulation.
- 5.1.5. In addition to the mark prescribed in paragraph 4.1., an approval mark as described in paragraphs 5.2. and 5.3. below shall be affixed in the spaces referred to in paragraph 4.2. above to every headlamp conforming to a type of HSB unit approved under this Regulation.
- 5.2. Composition of the approval mark
- The approval mark shall consist of:
- 5.2.1. an international approval marking, comprising
- 5.2.1.1. a circle surrounding the letter "E" followed by the distinguishing number of the country which has granted approval; 3/
- 5.2.1.2. the approval number prescribed in paragraph 5.1.3. above;

---

3/ 1 for Germany, 2 for France, 3 for Italy, 4 for the Netherlands, 5 for Sweden, 6 for Belgium, 7 for Hungary, 8 for the Czech and Slovak Federal Republic, 9 for Spain, 10 for Yugoslavia, 11 for the United Kingdom, 12 for Austria, 13 for Luxembourg, 14 for Switzerland, 15 (vacant), 16 for Norway, 17 for Finland, 18 for Denmark, 19 for Romania, 20 for Poland, 21 for Portugal and 22 for the Russian Federation. Subsequent numbers will be assigned to other countries in the chronological order in which they ratify or accede to the Agreement concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, and the numbers thus assigned shall be communicated by the Secretary-General of the United Nations to the Contracting Parties to the Agreement.



- 5.2.2. the following additional symbol (or symbols):
- 5.2.2.1. on HSB optical units meeting left-hand traffic requirements only, a horizontal arrow, pointing to the right of an observer, facing the HSB optical unit, i.e., to the side of the road on which the traffic moves;
  - 5.2.2.2. on HSB optical units meeting the requirements of this Regulation in respect of the passing beam only, the letters "HSC";
  - 5.2.2.3. on HSB optical units meeting the requirements of this Regulation in respect of the driving beam only, the letters "HSR";
  - 5.2.2.4. on HSB optical units meeting the requirements of this Regulation in respect of both the passing beam and the driving beam, the letters "HSCR";
  - 5.2.2.5. on HSB optical units meeting the requirements of this Regulation in respect of the driving beam, an indication of the maximum luminous intensity expressed by a reference mark, as defined in paragraph 8.3.2.1.2. below, placed near the circle surrounding the letter "E";
  - 5.2.2.6. on HSB units incorporating a lens of plastic material, the group of letters "PL" near the symbols prescribed in paragraphs 5.2.2.3. to 5.2.2.5. above;
  - 5.2.2.7. the two digits of the approval number (at present 02) which indicate the series of amendments incorporating the most recent major technical amendments made to the Regulation at the time of issue of the approval and, if necessary, the required arrow may be marked close to the above additional symbols.
  - 5.2.2.8. In every case the relevant operating mode used during the test procedure according to paragraph 1.1.1.1. of annex 6 and the allowed voltage(s) according to paragraph 1.1.1.2. of annex 6 shall be stipulated on the approval forms and on the communication forms transmitted to the countries which are Contracting Parties to the Agreement and which apply this Regulation.

In the corresponding cases the device shall be marked as follows:

On units meeting the requirements of this Regulation which are so designed that the filament of the passing beam shall not be lit simultaneously with that of any other lighting function with which it may be reciprocally incorporated:

an oblique stroke (/) shall be placed behind the passing lamp symbol in the approval mark.

5.2.2.9. The marks and symbols referred to in paragraphs 5.2.1. and 5.2.2. above shall be clearly legible and be indelible even when the optical unit is fitted in the vehicle.

5.3. Arrangement of the approval mark

5.3.1. Independent lamps

Annex 2, figures 1 to 7, to this Regulation gives examples of arrangements of the approval mark with the above-mentioned additional symbols.

5.3.2. Grouped, combined or reciprocally incorporated lamps

5.3.2.1. Where grouped, combined or reciprocally incorporated lamps have been found to comply with the requirements of several Regulations, a single international approval mark may be affixed, consisting of a circle surrounding the letter "E" followed by the distinguishing number of the country which has granted the approval, and an approval number. This approval mark may be located anywhere on the grouped, combined or reciprocally incorporated lamps, provided that:

5.3.2.1.1. it is visible after their installation;

5.3.2.1.2. no part of the grouped, combined or reciprocally incorporated lamps that transmits light can be removed without at the same time removing the approval mark.

5.3.2.2. The identification symbol for each lamp appropriate to each Regulation under which approval has been granted, together with the corresponding series of amendments incorporating the most recent major technical amendments to the Regulation at the time of issue of the approval and, if necessary, the required arrow shall be marked:

5.3.2.2.1. either on the appropriate light-emitting surface,

5.3.2.2.2. or in a group, in such a way that each of the grouped, combined or reciprocally incorporated lamps may be clearly identified (see four possible examples in annex 2).

5.3.2.3. The size of the components of a single approval mark shall not be less than the minimum size required for the smallest of the individual marks by the Regulation under which approval has been granted.

5.3.2.4. An approval number shall be assigned to each type approved. The same Contracting Party may not assign the same number to another type of grouped, combined or reciprocally incorporated lamps covered by this Regulation.

5.3.2.5. Annex 2, figure 8, to this Regulation gives examples of arrangements of approval marks for grouped, combined or reciprocally incorporated lamps with all the above-mentioned additional symbols.

5.3.3. Lamps, the lens of which is used for different types of lamps and which may be reciprocally incorporated or grouped with other lamps

The provisions laid down in paragraph 5.3.2. above are applicable.

5.3.3.1. In addition, where the same lens is used, the latter may bear the different approval marks relating to the different types of headlamps or units of lamps, provided that the main body of the HSB unit, even if it cannot be separated from the lens, also comprises the space described in paragraph 4.2. above and bears the approval mark of the actual functions.

If different types of HSB units comprise the same main body, the latter may bear the different approval marks.

5.3.3.2. Annex 2, figure 9, to this Regulation gives examples of arrangements of approval marks relating to the above case.

## 6. GENERAL SPECIFICATIONS

6.1. Every sample shall conform to the specifications set forth in this paragraph and in paragraphs 7. and 8. below and, if necessary, to those set forth in paragraph 9.

6.2. HSB units shall be so designed and made that in normal use, despite the vibrations to which they may then be subjected, their satisfactory operation continues to be ensured and they retain the characteristics prescribed by this Regulation.

6.2.1. HSB optical units shall be fitted with a device enabling them to be so adjusted on the vehicle as to comply with the rules applicable to them. Such a device need not be fitted on HSB optical unit insert if the use of such inserts is confined to vehicles on which the headlamp setting can be adjusted by other means.

Where an HSB optical unit providing a driving beam and an HSB optical unit providing a passing beam are assembled as exchangeable subunits to form a composite unit, the adjusting device shall enable each HSB unit individually to be duly adjusted.

6.2.2. However, this will not apply to headlamp assemblies whose reflectors are indivisible. For this type of assembly the requirements of paragraph 8.3. of this Regulation shall apply. In the case where more than one light source is used to provide the main beam, the combined main-beam functions will be used to determine the maximum value of the illumination ( $E_M$ ).

- 6.3. The terminals shall be in electrical contact with the appropriate filament or filaments only and shall be robust and firmly fixed to the HSB unit.
- 6.4. HSB units shall comprise electrical connections in conformity with those shown in one of the patterns reproduced in annex 3 to this Regulation and shall be of the dimensions specified in that annex.
- 6.5. Complementary tests shall be done according to the requirements of annex 6 to ensure that in use there is no excessive change in photometric performance.
- 6.6. If the lens of the HSB unit is of plastic material, tests shall be done according to the requirements of annex 7.
7. RATED AND TEST VALUES
- 7.1. The rated voltage is 12 volts. 4/
- 7.2. The wattage shall not exceed 75 watts on the driving beam filament and 68 watts on the passing beam filament measured at a test voltage of 13.2 volts.
8. ILLUMINATION 5/
- 8.1. General specifications
- 8.1.1. HSB units shall be made so as to give adequate illumination without dazzle when emitting the passing beam and good illumination when emitting the driving beam.
- 8.1.2. The illumination produced by the HSB unit shall be determined by means of a vertical screen set up 25 m forward of the unit as shown in annex 4 to this Regulation. 6/

---

4/ Requirements for HSB units with a rated voltage of 24 volts are under consideration.

5/ All photometric measurements shall be made at the rated voltage specified in paragraph 7.1.

6/ If, in the case of an HSB unit designed to meet the requirements of this Regulation in respect of the passing beam only, the focal axis diverges appreciably from the general direction of the beam, lateral adjustment shall be effected in the manner which best satisfies the requirements for illumination at points 75 R and 50 R for right-hand traffic and 75 L and 50 L for left-hand traffic.

- 8.1.3. On this screen, the illumination referred to in paragraphs 8.2.5., 8.2.6. and 8.3. below shall be measured by means of a photoreceptor, the effective area of which shall be contained within a square of 65 mm side.
- 8.2. Requirements concerning the passing beam
- 8.2.1. The passing beam shall produce a "cut-off" sharp enough to serve as a satisfactory means of adjustment. The "cut-off" shall be a horizontal straight line on the side opposite to the direction of the traffic for which the unit is intended. On the other side it shall not extend beyond either the broken line HV H<sub>1</sub> H<sub>4</sub> formed by a straight line HV H<sub>1</sub> making a 45° angle with the horizontal and a straight line H<sub>1</sub> H<sub>4</sub>, 25 cm above the straight line hh, or the straight line HV H<sub>3</sub>, inclined at an angle of 15° above the horizontal (see annex 4 to this Regulation). A "cut-off" extending beyond both line HV H<sub>2</sub> and line H<sub>2</sub> H<sub>4</sub> and resulting from a combination of the above two possibilities shall in no circumstances be permitted.
- 8.2.2. The HSB unit shall be so aimed that on the passing beam:
- 8.2.2.1. in the case of HSB units designed to meet the requirements of right-hand traffic, the "cut-off" on the left half of the screen 7/ is horizontal and, in the case of HSB units designed to meet the requirements of left-hand traffic, the "cut-off" on the right half of the screen is horizontal;
- 8.2.2.2. this horizontal part of the "cut-off" is situated on the screen 25 cm below the level hh (see annex 4 to this Regulation);
- 8.2.2.3. The "elbow" of the "cut-off" is on line vv. 8/
- 8.2.3. When so adjusted, the HSB unit need meet only the requirements laid down in paragraphs 8.2.5. and 8.2.6. below if approval thereof is sought solely for provision of a passing beam; 9/ if it is

---

7/ The test screen shall be wide enough to allow examination of the "cut-off" over a range of at least 5° on either side of the line vv.

8/ If the beam does not have a "cut-off" with a clear "elbow", lateral adjustment shall be effected in the manner which best satisfies the requirements for illumination at points 75 R and 50 R for right-hand traffic and 75 L and 50 L for left-hand traffic.

9/ An HSB unit designed to emit a passing beam may incorporate a driving beam not subject to this specification.

intended to provide both a passing beam and a driving beam it shall meet the requirements laid down in paragraphs 8.2.5., 8.2.6. and 8.3.

- 8.2.4. Where an HSB unit so adjusted does not meet the requirements laid down in paragraphs 8.2.5., 8.2.6. and 8.3., its alignment may be changed provided that the axis of the beam is not displaced laterally by more than  $1^\circ$  (= 44 cm) to the right or left. 10/ To facilitate alignment by means of the "cut-off", the unit may be partially occulted in order to sharpen the "cut-off".
- 8.2.5. The illumination produced on the screen by the passing beam shall meet the following requirements:

POINT ON MEASURING SCREEN		REQUIRED ILLUMINATION IN LUX
HSB UNITS FOR RIGHT-HAND TRAFFIC	HSB UNITS FOR LEFT-HAND TRAFFIC	
B 50 L	B 50 R	$\leq 0.4$
75 L	75 L	$\geq 12$
75 L	75 R	$\leq 12$
50 L	50 R	$\geq 12$
50 R	50 L	$\leq 15$
50 V	50 V	$\geq 6$
25 L	25 R	$\geq 2$
25 R	25 L	$\geq 2$
		$\leq 0.7$
		$\geq 3$
Any point in zone III		$\leq 2 \times (E_{50R} \text{ or } * E_{50L})$
" " " " IV		
" " " " I		

\*  $E_{50R}$  and  $E_{50L}$  are the illuminations actually measured.

- 8.2.6. There shall be no lateral variations detrimental to good visibility in any of the Zones I, II, III and IV.
- 8.3. Requirements concerning the driving beam
- 8.3.1. In the case of an HSB unit designed to provide a driving beam and a passing beam, measurements of the illumination produced on the

---

10/ The limit of realignment of  $1^\circ$  to the right or left is not incompatible with vertical realignment upward or downward. The latter is limited only by the requirements of paragraph 8.3. However, the horizontal part of the "cut-off" should not extend beyond the line hh (the provisions of paragraph 8.3. are not applicable to HSB units intended to meet the requirements of this Regulation only for provision of a passing beam).

screen by the driving beam shall be taken with the same HSB unit alignment as for measurements under paragraphs 8.2.5. and 8.2.6.; if the HSB unit provides a driving beam only, it shall be so adjusted that the area of maximum illumination is centred on the point of intersection HV of lines hh and vv; such an HSB unit need meet only the requirements laid down in paragraph 8.3.

8.3.2. The illumination produced on the screen by the driving beam shall meet the following requirements:

8.3.2.1. The point of intersection HV of lines hh and vv shall be situated within the isolux 80% of maximum illumination. This maximum value ( $E_M$ ) shall not be less than 48 lux. The maximum value ( $E_M$ ) shall not exceed 240 lux; in addition, in the case of a combined passing and driving HSB unit, it shall in no case exceed 16 times the illumination measured for the passing beam at point 75 R (or 75 L).

8.3.2.1.1. The maximum intensity ( $I_M$ ) of the driving beam expressed in thousands of candelas shall be calculated by the formula:

$$I_M = 0.625 E_M$$

8.3.2.1.2. The reference mark ( $I'_M$ ) of this maximum intensity, referred to in paragraph 5.2.2.5., shall be obtained by the ratio:

$$I'_M = \frac{I_M}{3} = 0.208 E_M$$

This value shall be rounded off to the nearest value 7.5 - 10 - 12.5 - 17.5 - 20 - 25 - 27.5 - 30 - 37.5 - 40 - 45 - 50.

8.3.2.2. Starting from point HV, horizontally to the right and left, the illumination shall be not less than 24 lux up to a distance of 1.125 m and not less than 6 lux up to a distance of 2.25 m.

9. COLOUR

9.1. Approval may be obtained for HSB units emitting either white or selective yellow light. <sup>11/</sup> Expressed in CIE trichromatic coordinates, the corresponding colorimetric characteristics for selective yellow light are as follows at the test voltage:

---

<sup>11/</sup> Notwithstanding the provisions of article 3 of the 1958 Agreement concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, the approval of an HSB unit under this Regulation shall not prevent the Contracting Parties to the Agreement applying this Regulation from prohibiting, on vehicles registered in their territory, the use of HSB units emitting a beam of either white or selective yellow light.

Limit towards red	$y \geq 0.138 + 0.580x$
Limit towards green	$y \leq 1.290x - 0.100$
Limit towards white	$y \geq -x + 0.966$
Limit towards spectral value	$y \leq -x + 0.992$

which can be expressed as follows:

dominant wave length	:	575 to 585 nm
purity factor	:	0.90 to 0.98

- 9.2. The illumination produced on the screen by a selective yellow passing beam shall meet the requirements of paragraphs 8.2.5. and 8.2.6. with the minimum illuminations multiplied by a factor of 0.85; the maximum illumination values remain the same.
10. GAUGING OF DISCOMFORT
- The discomfort caused by the passing beam of HSB units shall be gauged. 12/
11. CONFORMITY OF PRODUCTION
- Every HSB unit bearing an approval mark as provided for in this Regulation shall conform to the approval type and meet the requirements stated. Compliance with this provision shall be verified in accordance with annex 5 to this Regulation and if applicable paragraph 3 of annex 7 to this Regulation.
12. PENALTIES FOR NON-CONFORMITY OF PRODUCTION
- 12.1. The approval granted in respect of a type of HSB unit pursuant to this Regulation may be withdrawn if the requirements set forth above are not met, or if an HSB unit bearing the approval mark does not conform to the type approved.
- 12.2. If a Contracting Party to the Agreement applying this Regulation withdraws an approval it has previously granted, it shall forthwith so notify the other Contracting Parties applying this Regulation, by means of a communication form conforming to the model in annex 1 to this Regulation.

---

12/ This requirement will be subject to a recommendation to administrations.



13. MODIFICATION AND EXTENSION OF APPROVAL OF A TYPE OF HALOGEN SEALED-BEAM HEADLAMP UNIT (HSB UNIT)
- 13.1. Every modification of the type of HSB unit shall be notified to the administrative department which approved the type of HSB unit. The department may then either:
- 13.1.1. Consider that the modifications made are unlikely to have an appreciable adverse effect and that in any case the HSB unit still complies with the requirements; or
- 13.1.1. Require a further test report from the technical service responsible for conducting the tests.
- 13.2. Confirmation or refusal of approval, specifying the alterations shall be communicated by the procedure specified in paragraph 5.1.4. above to the Parties to the Agreement applying this Regulation.
- 13.3. The competent authority issuing the extension of approval shall assign a series number for such an extension and inform thereof the other Parties to the 1958 Agreement applying this Regulation by means of a communication form conforming to the model in annex 1 to this Regulation.
14. PRODUCTION DEFINITELY DISCONTINUED
- If the holder of an approval completely ceases to manufacture a type of HSB unit approved in accordance with this Regulation, he shall so inform the authority which granted the approval. Upon receiving the relevant communication, that authority shall inform thereof the other Parties to the 1958 Agreement applying this Regulation by means of a communication form conforming to the model in annex 1 to this Regulation.
15. TRANSITIONAL PROVISIONS
- 15.1. As from the date of entry into force of the 02 series of amendments to this Regulation no Contracting Party applying it shall refuse to grant approvals under this Regulation as amended by the 02 series of amendments.
- 15.2. As from 24 months after the date of entry into force mentioned in paragraph 15.1. above, Contracting Parties applying this Regulation shall grant approvals only if the type of HSB unit corresponds to the requirements of this Regulation as amended by the 02 series of amendments.
- 15.3. Existing approvals granted under this Regulation before the date mentioned in paragraph 15.2. above shall remain valid. However,

Contracting Parties applying this Regulation may prohibit the fitting of HSB units which do not meet the requirements of this Regulation as amended by the 02 series of amendments:

- 15.3.1. on vehicles for which type approval or individual approval is granted more than 24 months after the date of entry into force mentioned in paragraph 15.1. above,
- 15.3.2. on vehicles first registered more than five years after the date of entry into force mentioned in paragraph 15.1. above.

16. NAMES AND ADDRESSES OF TECHNICAL SERVICES RESPONSIBLE FOR CONDUCTING APPROVAL TESTS AND OF ADMINISTRATIVE DEPARTMENTS


The Parties to the 1958 agreement applying this Regulation shall communicate to the United Nations Secretariat the names and addresses of the technical services responsible for conducting approval tests and of the administrative departments which grant approval and to which forms certifying approval or extension or refusal or withdrawal of approval, or production definitely discontinued, issued in other countries, are to be sent.

---

Annex 1

COMMUNICATION

(maximum format: A4 (210 x 297mm))



issued by: Name of administration:

.....  
.....  
.....

concerning: 2/ APPROVAL GRANTED  
APPROVAL EXTENDED  
APPROVAL REFUSED  
APPROVAL WITHDRAWN  
PRODUCTION DEFINITELY DISCONTINUED

of a type of: Halogen Sealed-Beam Headlamp Unit (HSB unit)  
pursuant to Regulation No. 31

Approval No. ...

Extension No. ....

1. HSB unit submitted for approval as type 3/ .....  
Colour of light emitted: white/selective yellow 2/ .....  
Rated voltage .....  
Rated wattage .....
2. The passing lamp filament may/may not 2/ be lit simultaneously with the  
driving lamp filament and/or another reciprocally incorporated lamp .....  
.....
3. Trade name or mark .....
4. Manufacturer's name and address .....
5. If applicable, name and address of manufacturer's representative  
.....
6. Submitted for approval on .....

7. Technical service responsible for conducting approval tests  
.....
8. Date of report issued by that service .....
9. Number of report issued by that service .....
10. Approval granted/extended/refused/withdrawn 2/ .....
11. Reason(s) of extension (if applicable) .....
12. Maximum illumination (in lux) of the driving beam at 25 m from  
the HSB unit ..... (average for 5 units)
13. Place .....
14. Date .....
15. Signature .....
16. The attached drawing No. .... shows the unit.

#### Notes

1/ Distinguishing number of the country which has granted/extended/  
refused/withdrawn approval (see approval provisions in the Regulation).

2/ Strike out what does not apply.

3/ Indicate the appropriate marking selected from the list below:

HSCR, HSCR, HSCR, HSC, HSC, HSC, HSR, HSC/R, HSC/R, HSC/R, HSC/, HSC/,  
→ ← → > < → → ← → →  
HSC/, HSCR PL, HSCR PL, HSCR PL, HSC PL, HSC PL, HSC PL, HSC PL, HSR PL,  
← → → ← → → → ← →  
HSC/R PL, HSC/R PL, HSC/PL, HSC/PL, HSC/PL  
→ ← → → < >

---

Annex 2

EXAMPLES OF ARRANGEMENTS OF APPROVAL MARKS




Figure 1

The above approval mark affixed to an HSB optical unit indicates that the unit concerned was approved in the Netherlands (E4) under number 2439, that it meets the requirements of this Regulation, as amended by the 02 series of amendments, in respect of both the driving beam and the passing beam, and that it is designed for right-hand traffic only.

The figure 30 indicates that the maximum intensity of the driving beam is between 86,250 and 101,250 candelas.

Note: The approval number and the additional symbol(s) shall be placed close to the circle and either above or below the letter "E", or to the right or left of that letter. The digits of the approval number shall be on the same side of the letter "E" and face the same direction. The use of Roman numerals as approval numbers should be avoided so as to prevent any confusion with other symbols.




Figure 2

The above approval mark affixed to an HSB optical unit indicates that the unit concerned meets the requirements of this Regulation as amended by the 02 series of amendments, with respect to both the passing beam and the driving beam and that it is designed for left-hand traffic only.




Figure 3 a

The above approval mark affixed to an HSB optical unit indicates that the unit concerned meets the requirements of this Regulation as amended by the 02 series of amendments, in respect of the passing beam only, and that it is designed for right-hand traffic only.



Figure 3 b




Figure 4

The above approval marks affixed to HSB optical units incorporating the lens of plastic material indicate that the units concerned meet the requirements of this Regulation, as amended by the 02 series of amendments:

With respect to the passing beam only, and that they are designed for left-hand traffic only.




Figure 5

With respect to the driving beam only.

The number 30 indicates that the maximum intensity of the driving beam is between 82,500 and 101,250 candelas.

HSC/R  
02



2439

HSC/



02 2439

Figure 6

Identification of an HSB unit meeting  
the requirements of Regulation No. 31

with respect to both the passing beam  
and the driving beam and designed for  
right-hand traffic only.

Figure 7

with respect to the passing beam  
only and designed for right-hand  
traffic only.


The passing lamp filament shall not be lit  
simultaneously with the driving lamp  
filament and/or another reciprocally  
incorporated lamp.



Figure 8

Simplified marking for grouped, combined or  
reciprocally incorporated lamps

(The vertical and horizontal lines schematize the shape of the light-signalling device. They are not part of the approval mark.)



Note: The four examples shown above correspond to a lighting device bearing an approval mark relating to:

A front position lamp approved in accordance with the 01 series of amendments to Regulation No. 7;

An HSB optical unit with a passing beam designed for right-hand and left-hand traffic and a driving beam with a maximum intensity comprised between 86,250 and 101,250 candelas (as indicated by the number 30), approved in accordance with the 02 series of amendments to Regulation No. 31 and incorporating a lens of plastic material;


A front fog lamp approved in accordance with the 02 series of amendments to Regulation No. 19 and incorporating a lens of plastic material;

A front direction indicator lamp of category 1a, approved in accordance with the 02 series of amendments to Regulation No. 6.

Figure 9

Lamp reciprocally incorporated with an HSB unit

Example 1




The above example corresponds to the marking of a lens of plastic material intended to be used in different types of HSB units, namely:

- either: an HSB unit with a passing beam designed for right-hand and left-hand traffic and a driving beam approved in Germany (E1) in accordance with the requirements of Regulation No. 5 as amended by the 02 series of amendments, which is reciprocally incorporated with a front position lamp approved in accordance with the 01 series of amendments to Regulation No. 7;
- or: an HSB unit with a passing beam designed for right-hand and left-hand traffic and a driving beam with a maximum intensity comprised between 86,250 and 101,250 candelas, approved in Germany (E1) in accordance with the requirements of


Germany (E1) in accordance with the requirements of Regulation No. 31 as amended by the 02 series of amendments which is reciprocally incorporated with the same front position lamp as above;

or even: either of the above-mentioned HSB units approved as a single lamp.

The main body of the optical unit shall bear the only valid approval number, for instance:



Example 2



The above example corresponds to the marking of a lens used in an assembly of two HSB optical units approved in the Netherlands (E4), consisting of a headlamp emitting a passing beam designed for both traffic systems and of a driving beam meeting the requirements of Regulation No. 1, and of a headlamp emitting a driving beam meeting the requirements of Regulation No. 31.

Annex 3

ELECTRICAL CONNECTIONS OF HSB UNITS

Category 1  
(Driving only)




Fig. 1

Category 21  
(Passing only)





Fig.2

Category 22  
(Passing and driving)




(Dimensions in mm)

Fig. 3

## Annex 4

## MEASURING SCREEN


### A. HSB unit for right-hand traffic



### h-h: horizontal plane) passing through

v-v: vertical plane ) focus of HSB unit

Axis of road /





Annex 5

VERIFICATION OF CONFORMITY OF PRODUCTION OF HSB UNITS

1. HSB units bearing an approval mark shall conform to the approved type.
2. Conformity shall be deemed satisfactory from the mechanical and geometrical point of view if the differences do not exceed the tolerances indicated on the drawings in annex 3 to this Regulation.
3. As regards photometric performance, the conformity of serially manufactured units shall not be contested if at least 90% of HSB units in a sample taken at random satisfy one of the following requirements: either
  - 3.1. none of the values measured deviates unfavourably by more than 20% from the prescribed value. (For values B 50 R or L and zone III, the maximum unfavourable deviation permitted shall be 0.2 lux (B 50 R or L) or 0.3 lux (zone III)), or
  - 3.2. for the passing beam, the prescribed values are met at HV (with a tolerance of 0.2 lux) and at one point at least of the area delimited on the measuring screen (at 25 m) by a circle of 15 cm radius around points B 50 R or L (with a tolerance of 0.1 lux), 75 R or L, 50 R or L, 25 L or R and in the entire area of zone IV which is not more than 22.5 cm above line 25 R and 25 L and if, for the driving beam, HV being situated within the isolux 0.75 E max., a tolerance of 20% is observed for the photometric values. 1/
4. See also annex 6, paragraph 3, and if applicable annex 7, paragraph 3 to this Regulation.

Note

1/ The maximum value (16) prescribed in paragraph 8.3.2.1. of this Regulation for the ratio of maximum illumination of the driving beam to illumination at point 75 R (or 75 L) is checked solely for the purpose of seeing whether the "type" of HSB unit has the desired characteristics; no such check need be made during verification of conformity of production.

---

Annex 6

TESTS FOR STABILITY OF PHOTOMETRIC PERFORMANCE  
OF HEADLAMPS IN OPERATION

TESTS ON COMPLETE HEADLAMPS

Once the photometric values have been measured according to the prescriptions of this Regulation, in points for  $E_{\max}$  for driving beam and HV, 50 R, B 50 L for passing beam (or HV, 50 L, B 50 R for headlamps designed for left-hand traffic) a complete headlamp sample shall be tested for stability of photometric performance in operation. "Complete headlamp" shall be understood to mean the complete lamp itself including those surrounding body parts and lamps which could influence its thermal dissipation.

1. TEST OF STABILITY OF PHOTOMETRIC PERFORMANCE

The tests shall be carried out in a dry and still atmosphere at an ambient temperature of  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , the complete headlamp being mounted on a base representing the correct installation on the vehicle.

1.1. Clean headlamp

The headlamp shall be operated for 12 hours as described in subparagraph 1.1.1. and checked as prescribed in subparagraph 1.1.2.

1.1.1. Test procedure

The headlamp shall be operated for a period according to the specified time, so that:

- 1.1.1.1. (a) in the case where only one lighting function (driving or passing beam) is to be approved, the corresponding filament is lit for the prescribed time, 2/
- (b) in the case of a reciprocally incorporated passing lamp and driving lamp (dual filament HSB headlamp):

If the applicant declares that the headlamp is to be used with a single filament lit 1/ at a time, the test shall be carried out in accordance with this condition, activating 2/ each specified function successively for half the time specified in paragraph 1.1.;

In all other cases 1/ 2/ the headlamp, shall be subjected to the following cycle until the time specified is reached:

15 minutes, passing-beam filament lit  
5 minutes, all filaments lit.

- (c) in the case of grouped lighting functions all the individual functions shall be lit simultaneously for the time specified for individual lighting functions (a) also taking into account the use of reciprocally incorporated lighting functions (b), according to the manufacturer's specifications.

1.1.1.2. Test voltage

The voltage shall be adjusted so as to supply 90% of the maximum wattage specified in this Regulation for the type(s) of HSB headlamp(s) concerned is (are) obtained.

1.1.2. Test results

1.1.2.1. Visual inspection

Once the headlamp has been stabilized to the ambient temperature, the headlamp lens and the external lens, if any, shall be cleaned with a clean, damp cotton cloth. It shall then be inspected visually; no distortion, deformation, cracking or change in colour of either the headlamp lens or the external lens, if any, shall be noticeable.

1.1.2.2. Photometric test

To comply with the requirements of this Regulation, the photometric values shall be verified in the following points:

Passing beam:

50 R - B 50 L - HV for headlamps designed for right-hand traffic  
50 L - B 50 R - HV for headlamps designed for left-hand traffic

Driving beam:

Point of  $E_{max}$

Another aiming may be carried out to allow for any deformation of the headlamp base due to heat (the change of the position of the cut-off line is covered in para. 2 of this annex);

A 10% discrepancy between the photometric characteristics and the values measured prior to the test is permissible including the tolerances of the photometric procedure.

1.2. Dirty headlamp

After being tested as specified in subparagraph 1.1. above, the headlamp shall be operated for one hour as described in subparagraph 1.1.1., after being prepared as prescribed in subparagraph 1.2.1., and checked as prescribed in subparagraph 1.1.2.

1.2.1. Preparation of the headlamp

1.2.1.1. Test mixture

The mixture of water and a polluting agent to be applied to the headlamp shall be composed of nine parts (by weight) of silica sand with a grain size distributed between 0 and 100  $\mu\text{m}$ , one part (by weight) of vegetal carbon dust of a grain size distributed between 0 and 100  $\mu\text{m}$ , 0.2 part (by weight) of NaCMC 3/ and an appropriate quantity of distilled water, the conductivity of which is lower than 1 mS/m for the purpose of this test.

The mixture must not be more than 14 days old.

1.2.1.2. Application of the test mixture to the headlamp

The test mixture shall be uniformly applied to the entire light emitting surface of the headlamp and then left to dry. This procedure shall be repeated until the illumination value has dropped to 15-20% of the values measured for each following point under the conditions described in paragraph 1 above:

Point of  $E_{\text{max}}$  in driving beam, photometric distribution for a driving/passing lamp,

Point of  $E_{\text{max}}$  in driving beam, photometric distribution for a driving lamp only,

50 R and 50 V 4/ for a passing lamp only, designed for right-hand traffic,

50 L and 50 V 4/ for a passing lamp only, designed for left-hand traffic.

1.2.1.3. Measuring equipment

The measuring equipment shall be equivalent to that used during headlamp approval tests.

2. TEST FOR CHANGE IN VERTICAL POSITION OF THE CUT-OFF LINE UNDER THE INFLUENCE OF HEAT

This test consists of verifying that the vertical drift of the cut-off line under the influence of heat does not exceed a specified value for an operating passing lamp.

The headlamp tested in accordance with paragraph 1.1., shall be subjected to the test described in 2.1., without being removed from or readjusted in relation to its test fixture.

2.1. Test

The test shall be carried out in a dry and still atmosphere at an ambient temperature of  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ .

Using a mass production HSB headlamp which has been aged for at least one hour the headlamp shall be operated on passing beam without being dismantled from or readjusted in relation to its test fixture. (For the purpose of this test, the voltage shall be adjusted as specified in para. 1.1.1.2.). The position of the cut-off line in its horizontal part (between vv and the vertical line passing through point B 50 L for right-hand traffic or B 50 R for left-hand traffic) shall be verified 3 minutes ( $r_3$ ) and 60 minutes ( $r_{60}$ ) respectively after operation.

The measurement of the variation in the cut-off line position as described above shall be carried out by any method giving acceptable accuracy and reproducible results.

2.2. Test results

2.2.1. The result expressed in milliradians (mrad) shall be considered as acceptable when the absolute value  $\Delta r_I = |r_3 - r_{60}|$  recorded on the headlamp is not more than 1.0 mrad ( $\Delta r_I \leq 1.0 \text{ mrad}$ ).

2.2.2. However, if this value is more than 1.0 mrad but not more than 1.5 mrad ( $1.0 \text{ mrad} < \Delta r_I \leq 1.5 \text{ mrad}$ ) a second headlamp shall be tested as described in 2.1. after being subjected three consecutive times to the cycle as described below, in order to stabilize the position of mechanical parts of the headlamp on a base representative of the correct installation on the vehicle:

Operation of the passing lamp for one hour, (the voltage shall be adjusted as specified in paragraph 1.1.1.2.),

Period of rest for one hour.

The headlamp type shall be considered as acceptable if the mean value of the absolute values  $\Delta r_I$  measured on the first sample and  $\Delta r_{II}$  measured on the second sample is not more than 1.0 mrad

$$\left( \frac{\Delta r_I + \Delta r_{II}}{2} \leq 1.0 \text{ mrad} \right)$$

### 3. CONFORMITY OF PRODUCTION

One of the sampled headlamps shall be tested according to the procedure described in paragraph 2.1. after being subjected three consecutive times to the cycle described in paragraph 2.2.2.

The headlamp shall be considered as acceptable if  $\Delta r$  does not exceed 1.5 mrad.

If this value exceeds 1.5 mrad but is not more than 2.0 mrad, a second headlamp shall be subjected to the test after which the mean of the absolute values recorded on both samples shall not exceed 1.5 mrad.

### Notes

1/ Should two filaments be simultaneously lit when headlamp flashing is used, this shall not be considered as being normal use of both filaments simultaneously.

2/ When the tested headlamp is grouped and/or reciprocally incorporated with signalling lamps, the latter shall be lit for the duration of the test. In the case of a direction indicator lamp, it shall be lit in flashing operation mode with an on/off time ratio of approximately one to one.

3/ NaCMC represents the sodium salt of carboxymethylcellulose, customarily referred to as CMC. The NaCMC used in the dirt mixture shall have a degree of substitution (DS) of 0.6-0.7 and a viscosity of 200-300 cP for a 2% solution at 20° C.

4/ 50 V is situated 375 mm below HV on the vertical line v-v on the screen at 25 m distance.

Annex 7

REQUIREMENTS FOR LAMPS INCORPORATING LENSES OF PLASTIC MATERIAL -  
TESTING OF LENS OR MATERIAL SAMPLES AND OF COMPLETE LAMPS

1. GENERAL SPECIFICATIONS

- 1.1. The samples supplied pursuant to paragraph 2.2.4. of Regulations Nos. 1, 8, 19, 20 or paragraph 3.2.4. of Regulations Nos. 5, 31, 57, 72 shall satisfy the specifications indicated in paragraphs 2.1 to 2.5 below.
- 1.2. The two samples of complete lamps supplied pursuant to paragraph 2.2.3. of Regulations Nos. 1, 8, 19, 20 or paragraph 3.2.3. of Regulations Nos. 5, 31, 57, 72 and incorporating lenses of plastic material shall, with regard to the lens material, satisfy the specifications indicated in paragraph 2.6. below.
- 1.3. The samples of lenses of plastic material or samples of material shall be subjected, with the reflector to which they are intended to be fitted (where applicable), to approval tests in the chronological order indicated in table A reproduced in appendix 1 to this annex.
- 1.4. However, if the lamp manufacturer can prove that the product has already passed the tests prescribed in paragraphs 2.1.-2.5. below, or the equivalent tests pursuant to another Regulation, those tests need not be repeated; only the tests prescribed in appendix 1, table B, shall be mandatory.

2. TESTS

2.1. Resistance to temperature changes

2.1.1. Tests

Three new samples (lenses) shall be subjected to five cycles of temperature and humidity (RH = relative humidity) change in accordance with the following programme:

3 hours at  $40^{\circ}\text{C} \pm 2^{\circ}\text{C}$  and 85-95% RH;

1 hour at  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$  and 60-75% RH;

15 hours at  $-30^{\circ}\text{C} \pm 2^{\circ}\text{C}$ ;

1 hour at  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$  and 60-75% RH;

3 hours at  $80^{\circ} \text{C} \pm 2^{\circ} \text{C}$ ;

1 hour at  $23^{\circ} \text{C} \pm 5^{\circ} \text{C}$  and 60-75% RH;

Before this test, the samples shall be kept at  $23^{\circ} \text{C} \pm 5^{\circ} \text{C}$  and 60-75% RH for at least four hours.

Note: The periods of one hour at  $23^{\circ} \text{C} \pm 5^{\circ} \text{C}$  shall include the periods of transition from one temperature to another which are needed in order to avoid thermal shock effects.

#### 2.1.2. Photometric measurements

##### 2.1.2.1. Method

Photometric measurements shall be carried out on the samples before and after the test.

These measurements shall be made using a standard lamp, at the following points:

B 50 L and 50 R for the passing beam of a passing lamp or a passing/driving lamp (B 50 R and 50 L in the case of headlamps intended for left-hand traffic);

$E_{\text{max}}$  route for the driving beam of a driving lamp or a passing/driving lamp;

HV and  $E_{\text{max}}$  zone D for a front fog lamp.

##### 2.1.2.2. Results

The variation between the photometric values measured on each sample before and after the test shall not exceed 10% including the tolerances of the photometric procedure.

#### 2.2. Resistance to atmospheric and chemical agents

##### 2.2.1. Resistance to atmospheric agents

Three new samples (lenses or samples of material) shall be exposed to radiation from a source having a spectral energy distribution similar to that of a black body at a temperature between 5,500K and 6,000K. Appropriate filters shall be placed between the source and the samples so as to reduce as far as possible radiations with wave lengths smaller than 295 nm and greater than 2,500 nm. The samples shall be exposed to an energetic illumination of  $1,200 \text{ W/m}^2 \pm 200 \text{ W/m}^2$  for a period such that the luminous energy that they receive is equal to  $4,500 \text{ MJ/m}^2 \pm 200 \text{ MJ/m}^2$ . Within the



enclosure, the temperature measured on the black panel placed on a level with the samples shall be  $50^{\circ}\text{C} \pm 5^{\circ}\text{C}$ . In order to ensure a regular exposure, the samples shall revolve around the source of radiation at a speed between 1 and 5 1/min.

The samples shall be sprayed with distilled water of conductivity lower than 1 mS/m at a temperature of  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ , in accordance with the following cycle:

spraying: 5 minutes;  
drying: 25 minutes.

2.2.2. Resistance to chemical agents

After the test described in paragraph 2.2.1. above and the measurement described in paragraph 2.2.3.1. below have been carried out, the outer face of the said three samples shall be treated as described in paragraph 2.2.2.2. with the mixture defined in paragraph 2.2.2.1. below.

2.2.2.1. Test mixture

The test mixture shall be composed of 61.5% n-heptane, 12.5% toluene, 7.5% ethyl tetrachloride, 12.5% trichloroethylene and 6% xylene (volume per cent).

2.2.2.2. Application of the test mixture

Soak a piece of cotton cloth (as per ISO 105) until saturation with the mixture defined in paragraph 2.2.2.1. above and, within 10 seconds, apply it for 10 minutes to the outer face of the sample at a pressure of  $50\text{ N/cm}^2$ , corresponding to an effort of 100 N applied on a test surface of 14 x 14 mm.

During this 10-minute period, the cloth pad shall be soaked again with the mixture so that the composition of the liquid applied is continuously identical with that of the test mixture prescribed.

During the period of application, it is permissible to compensate the pressure applied to the sample in order to prevent it from causing cracks.

2.2.2.3. Cleaning

At the end of the application of the test mixture, the samples shall be dried in the open air and then washed with the solution described in paragraph 2.3. (Resistance to detergents) at  $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$ .

Afterwards the samples shall be carefully rinsed with distilled water containing not more than 0.2% impurities at  $23^{\circ} \text{C} \pm 5^{\circ} \text{C}$  and then wiped off with a soft cloth.

2.2.3. Results

2.2.3.1. After the test of resistance to atmospheric agents, the outer face of the samples shall be free from cracks, scratches, chipping and deformation, and the mean variation in transmission

$$\Delta t = \frac{T_2 - T_3}{T_2}, \text{ measured on the three samples according to the}$$

procedure described in appendix 2 to this annex shall not exceed 0.020

$$(\Delta t_m \leq 0.020).$$

2.2.3.2. After the test of resistance to chemical agents, the samples shall not bear any traces of chemical staining likely to cause a variation of flux diffusion, whose mean variation

$$\Delta d = \frac{T_5 - T_4}{T_2}, \text{ measured on the three samples according to the}$$

procedure described in appendix 2 to this annex shall not exceed 0.020

$$(\Delta d_m \leq 0.020).$$

2.3. Resistance to detergents and hydrocarbons

2.3.1. Resistance to detergents

The outer face of three samples (lenses or samples of material) shall be heated to  $50^{\circ} \text{C} \pm 5^{\circ} \text{C}$  and then immersed for five minutes in a mixture maintained at  $23^{\circ} \text{C} \pm 5^{\circ} \text{C}$  and composed of 99 parts distilled water containing not more than 0.02% impurities and one part alkylaryl sulphonate.

At the end of the test, the samples shall be dried at  $50^{\circ} \text{C} \pm 5^{\circ} \text{C}$ . The surface of the samples shall be cleaned with a moist cloth.

2.3.2. Resistance to hydrocarbons

The outer face of these three samples shall then be lightly rubbed for one minute with a cotton cloth soaked in a mixture composed of 70% n-heptane and 30% toluene (volume per cent), and shall then be dried in the open air.

2.3.3. Results

After the above two tests have been performed successively, the mean value of the variation in transmission

$\Delta t = \frac{T_2 - T_3}{T_2}$ , measured on the three samples according to the

procedure described in appendix 2 to this annex shall not exceed 0.010

( $\Delta t_m \leq 0.010$ ).

2.4. Resistance to mechanical deterioration

2.4.1. Mechanical deterioration method

The outer face of the three new samples (lenses) shall be subjected to the uniform mechanical deterioration test by the method described in appendix 3 to this annex.

2.4.2. Results

After this test, the variations:

in transmission:  $\Delta t = \frac{T_2 - T_3}{T_2}$ ,

and in diffusion:  $\Delta t = \frac{T_5 - T_4}{T_2}$ ,

shall be measured according to the procedure described in appendix 2 in the area specified in paragraph 2.2.4. above. The mean value of the three samples shall be such that:  $\Delta t_m \leq 0.100$ ;  
 $\Delta d_m \leq 0.050$ .

2.5. Test of adherence of coatings, if any

2.5.1. Preparation of the sample

A surface of 20 mm x 20 mm in area of the coating of a lens shall be cut with a razor blade or a needle into a grid of squares approximately 2 mm x 2 mm. The pressure on the blade or needle shall be sufficient to cut at least the coating.

2.5.2. Description of the test

Use an adhesive tape with a force adhesion of 2 N/(cm of width)  $\pm$  20% measured under the standardized conditions specified in appendix 4 to this annex. This adhesive tape, which shall be at least 25 mm wide, shall be pressed for at least five minutes to the surface prepared as prescribed in paragraph 2.5.1.

Then the end of the adhesive tape shall be loaded in such a way that the force of adhesion to the surface considered is balanced by a force perpendicular to that surface. At this stage, the tape shall be torn off at a constant speed of 1.5 m/s  $\pm$  0.2 m/s.

2.5.3. Results

There shall be no appreciable impairment of the gridded area. Impairments at the intersections between squares or at the edges of the cuts shall be permitted, provided that the impaired area does not exceed 15 per cent of the gridded surface.

2.6. Tests of the complete lamp incorporating a lens of plastic material

2.6.1. Resistance to mechanical deterioration of the lens surface

2.6.1.1. Tests

The lens of lamp sample No. 1 shall be subjected to the test described in paragraph 2.4.1. above.

2.6.1.2. Results

After the test, the results of photometric measurements carried out on the lamp in accordance with this Regulation shall not exceed by more than 30% the maximum values prescribed at points B 50 L and HV and not be more than 10% below the minimum values prescribed at point 75 R (in the case of headlamps intended for left-hand traffic, the points to be considered are B 50 R, HV and 75 L), in the case of front fog lamps this requirement shall be applied to zones A and B only.

2.6.2. Test of adherence of coatings, if any

The lens of lamp sample No. 2 shall be subjected to the test described in paragraph 2.5. above.

3. VERIFICATION OF THE CONFORMITY OF PRODUCTION

3.1. With regard to the materials used for the manufacture of lenses, the lamps of a series shall be recognized as complying with this Regulation if:

- 3.1.1. After the test for resistance to chemical agents and the test for resistance to detergents and hydrocarbons, the outer face of the samples exhibits no cracks, chipping or deformation visible to the naked eye (see paras. 2.2.2., 2.3.1. and 2.3.2.);
- 3.1.2. After the test described in paragraph 2.6.1.1., the photometric values at the points of measurement considered in paragraph 2.6.1.2. are within the limits prescribed for conformity of production by this Regulation.
- 3.2. If the test results fail to satisfy the requirements, the tests shall be repeated on another sample of headlamps selected at random.

## CHRONOLOGICAL ORDER OF APPROVAL TESTS

A. Tests on plastic materials (lenses or samples of material supplied pursuant to paragraph 2.2.4 (Regulations Nos. 1, 8, 19, 20; paragraph 3.2.4 in Regulations Nos. 5, 31, 57, 72) of this Regulation)

[illegible]

- B. Tests on complete headlamps (supplied pursuant to paragraph 2.2.3 (Regulations Nos. 1, 8, 19, 20; paragraph 3.2.3 in Regulations Nos. 5, 31, 57, 72) of this Regulation)

Tests	Complete headlamp	
	Sample No.	
	1	2
2.1. Deterioration (para. 2.6.1.1)	X	
2.2. Photometry (para. 2.6.1.2)	X	
2.3. Adherence (para. 2.6.2)		X

## Annex 7 - Appendix 2

### METHOD OF MEASUREMENT OF THE DIFFUSION AND TRANSMISSION OF LIGHT

#### 1. EQUIPMENT (see figure)

The beam of a collimator K with a half divergence  $\frac{\beta}{2} = 17.4 \times 10^{-4}$  rd is limited by a diaphragm  $D_T$  with an opening of 6 mm against which the sample stand is placed.

A convergent achromatic lens  $L_2$ , corrected for spherical aberrations, links the diaphragm  $D_T$  with the receiver R; the diameter of the lens  $L_2$  shall be such that it does not diaphragm the light diffused by the sample in a cone with a half top angle of  $\beta/2 = 14^\circ$ .

An annular diaphragm  $D_D$  with angles  $\frac{\alpha_0}{2} = 1^\circ$  and  $\frac{\alpha_{\max}}{2} = 12^\circ$  is placed in an image focal plane of the lens  $L_2$ .

The non-transparent central part of the diaphragm is necessary in order to eliminate the light arriving directly from the light source. It shall be possible to remove the central part of the diaphragm from the light beam in such a manner that it returns exactly to its original position.

The distance  $L_2 D_T$  and the focal length  $F_2$  1/ of the lens  $L_2$  shall be so chosen that the image of  $D_T$  completely covers the receiver R.

When the initial incident flux is referred to 1,000 units, the absolute precision of each reading shall be better than 1 unit.



#### 2. MEASUREMENTS

The following readings shall be taken:

Reading	With sample	With central part of $D_D$	Quantity represented
$T_1$	no	no	Incident flux in initial reading
$T_2$	yes (before test)	no	Flux transmitted by the new material in a field of $24^\circ$ C
$T_3$	yes (after test)	no	Flux transmitted by the tested material in a field of $24^\circ$ C
$T_4$	yes (before test)	yes	Flux diffused by the new material
$T_5$	yes (after test)	yes	Flux diffused by the tested material

1/ For  $L_2$  it is recommended to use a focal distance of about 80 mm.





Annex 7 - Appendix 3

SPRAY TESTING METHOD

1. Test equipment

1.1. Spray gun

The spray gun used shall be equipped with a nozzle 1.3 mm in diameter allowing a liquid flow rate of  $0.24 \pm 0.02$  l/minute at an operating pressure of 6.0 bars - 0, + 0.5 bar.

Under these operation conditions the fan pattern obtained shall be  $170 \text{ mm} \pm 50 \text{ mm}$  in diameter on the surface exposed to deterioration, at a distance of  $380 \text{ mm} \pm 10 \text{ mm}$  from the nozzle.

1.2. Test mixture

The test mixture shall be composed of:

Silica sand of hardness 7 on the Mohr scale, with a grain size between 0 and 0.2 mm and an almost normal distribution, with an angular factor of 1.8 to 2;

Water of hardness not exceeding  $205 \text{ g/m}^3$  for a mixture comprising 25 g of sand per litre of water.

2. Test

The outer surface of the lamp lenses shall be subjected once or more than once to the action of the sand jet produced as described above. The jet shall be sprayed almost perpendicular to the surface to be tested.

The deterioration shall be checked by means of one or more samples of glass placed as a reference near the lenses to be tested. The mixture shall be sprayed until the variation in the diffusion of light on the sample or samples measured by the method described in appendix 2, is such that:

$$\Delta d = \frac{T_5 - T_4}{T_2} = 0.0250 \pm 0.0025$$

Several reference samples may be used to check that the whole surface to be tested has deteriorated homogeneously.

Annex 7 - Appendix 4

ADHESIVE TAPE ADHERENCE TEST

1. PURPOSE

This method allows to determine under standard conditions the linear force of adhesion of an adhesive tape to a glass plate.

2. PRINCIPLE

Measurement of the force necessary to unstick an adhesive tape from a glass plate at an angle of 90°.

3. SPECIFIED ATMOSPHERIC CONDITIONS

The ambient conditions shall be at  $23^{\circ} \text{ C} \pm 5^{\circ} \text{ C}$  and  $65 \pm 15\%$  relative humidity (RH).

4. TEST PIECES

Before the test, the sample roll of adhesive tape shall be conditioned for 24 hours in the specified atmosphere (see para. 3 above).

Five test pieces each 400 mm long shall be tested from each roll. These test pieces shall be taken from the roll after the first three turns were discarded.

5. PROCEDURE

The test shall be under the ambient conditions specified in paragraph 3.

Take the five test pieces while unrolling the tape radially at a speed of approximately 300 mm/s, then apply them within 15 seconds in the following manner:

Apply the tape to the glass plate progressively with a slight lengthwise rubbing movement of the finger, without excessive pressure, in such a manner as to leave no air bubble between the tape and the glass plate.

Leave the assembly in the specified atmospheric conditions for 10 minutes.

Unstick about 25 mm of the test piece from the plate in a plane perpendicular to the axis of the test piece.

Fix the plate and fold back the free end of the tape at 90°. Apply force in such a manner that the separation line between the tape and the plate is perpendicular to this force and perpendicular to the plate.

Pull to unstick at a speed of 300 mm/s  $\pm$  30 mm/s and record the force required.

## 6. RESULTS

The five values obtained shall be arranged in order and the median value taken as the result of the measurement. This value shall be expressed in Newtons per centimetre of width of the tape.

- - - - -