



**Economic and Social  
Council**

Distr.

GENERAL

TRANS/WP.29/2001/45

17 August 2001

ENGLISH

Original: ENGLISH  
and FRENCH

**ECONOMIC COMMISSION FOR EUROPE**

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

(One-hundred-and-twenty-fifth session,  
6-9 November 2001, agenda item 5.2.7.)

PROPOSAL FOR DRAFT SUPPLEMENT 7 TO REGULATION No. 38

(Rear fog lamps)

Transmitted by the Working Party on Lighting  
and Light-Signalling (GRE)

Note: The text reproduced below was adopted by GRE at its forty-fourth session, however, a decision concerning its transmission for consideration to WP.29 and AC.1 has only been taken at the forty-sixth session. It is based on documents TRANS/WP.29/GRE/2000/4, not amended, and TRANS/WP.29/GRE/2000/5, as amended (TRANS/WP.29/GRE/44, paras. 19 and 21; TRANS/WP.29/GRE/46, para. 32).

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user. Documents are also available via the INTERNET:  
<http://www.unece.org/trans/main/welcwp29.htm>

Paragraph 2.1., amend to read:

"2.1. The application for approval shall be submitted by the holder of the trade name or mark or by his duly accredited representative.

At the choice of the applicant, it will specify that the device may be installed on the vehicle with different inclinations of the reference axis in respect to the vehicle reference planes and to the ground or rotate around its reference axis; these different conditions of installation shall be indicated in the communication form."

Paragraph 2.2.1., amend to read:

"..... and showing geometrically the position(s) in which the rear fog lamp may be fitted to the vehicle; the axis of ....."

Annex 1, item 9., amend to read:

"9. Concise description: 3/

Number and category of filament lamps: . . . . .

Geometrical conditions of installation and relating variations; if any: . . . . . "

Annex 3,

Insert a new paragraph 3., to read:

"3. In the case where the device may be installed on the vehicle in more than one or in a field of different positions the photometric measurements shall be repeated for each position or for the extreme positions of the field of the reference axis specified by the manufacturer."

Paragraphs 3. to 4.1. (former), renumber as paragraphs 4. to 5.1.

Paragraph 4.2., renumber as paragraph 5.2., and amend to read:

"5.2. For replaceable filament lamps:  
when equipped with filament lamps at 6.75 V, 13.5 V or 28.0 V the luminous intensity values produced shall be corrected. The correction factor is the ratio between the reference luminous flux and the mean value of the luminous flux found at the voltage applied (6.75 V, 13.5 V or 28.0 V). The actual luminous fluxes of each filament lamp used shall not deviate more than ± 5 per cent from the mean value. Alternatively a standard filament lamp may be used in turn, in each of the individual positions, operated at its reference flux, the individual measurements in each position being added together."

