



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/2002/16
19 December 2001

Original: ENGLISH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)
(One-hundred-and-twenty-sixth session,
12-15 March 2002, agenda item 4.2.8.)

DRAFT CORRIGENDUM 1 TO REVISION 1 (RUSSIAN ONLY) OF REGULATION No. 43
(Safety glazing)

Transmitted by the Working Party on General Safety Provisions (GRSG)

Note: The text reproduced below was adopted by GRSG at its eighty-first session, and is transmitted for consideration to WP.29 and to AC.1. It is based on document TRANS/WP.29/GRSG/2001/4, as corrected (TRANS/WP.29/GRSG/60, para. 26).

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user. Documents are also available via the INTERNET: <http://www.unece.org/trans/main/welcwp29.htm>

Annex 3,

Paragraph 2.1.4., correct to read (Russian only): 1/

"....

The point of impact shall be **within 25 mm** of the geometric centre of the test piece for a drop height less than or equal to 6 m, and **within 50 mm** of the centre of the test piece for a drop height greater than 6 m."

Paragraph 2.2.4., correct to read (Russian only):

"....

the point of impact shall be **within 25 mm** of the geometric centre of the test piece.

...."

Paragraph 3.3.1., footnote 1/ to Figure 3, correct the value of "3 Nm" to read "30 Nm" (Russian only).

Paragraph 3.3.1., correct to read (Russian only):

"....

The weight shall strike the test piece **within 40 mm** of its geometric centre on that face which represents the inward face of the safety-glass pane"

Paragraph 3.3.2., correct to read (Russian only):

"....

The headform weight shall strike the windscreen at a point **within 40 mm** of its geometric centre on that face which represents
