

14 October 2002

AGREEMENT

**CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS
FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED
AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR RECIPROCAL
RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF THESE PRESCRIPTIONS */**

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 86: Regulation No. 87

Amendment 4

Supplement 4 to the original version of the Regulation - Date of entry into force: 12 August 2002

**UNIFORM PROVISIONS CONCERNING THE APPROVAL OF DAYTIME RUNNING LAMPS
FOR POWER-DRIVEN VEHICLES**



UNITED NATIONS

*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.02-24431

Paragraph 3.1., amend to read:

A3.1. The application for approval shall be transmitted by the holder of the trade name or mark or by his duly accredited representative.

At the choice of the applicant, it will specify that the device may be installed on the vehicle with different inclinations of the reference axis in respect to the vehicle reference planes and to the ground or rotate around its reference axis; these different conditions of installation shall be indicated in the communication form.®

Paragraph 3.2.1., amend to read:

A... and showing geometrically the position(s) in which the daytime running lamp may be mounted on the vehicle; the axis of observation ...®

Paragraph 5.5.1.1., footnote 1/, amend to read:

"1/ ... 35 (vacant), 36 for Lithuania, ... 38 (vacant), 39 for Azerbaijan ... and 48 for New Zealand. Subsequent numbers"

Annex 1, item 9, amend to read:

A9. Concise description:
Number and category of filament lamps: 3/.....
Geometric conditions of installation and relating variations, if any:..... ®

Annex 3, add a new paragraph 3., to read:

A3. In the case where the daytime running lamp may be installed on the vehicle in more than one or in a field of different positions the photometric measurements shall be repeated for each position or for the extreme positions in the field of the reference axis specified by the manufacturer.®
