



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/902
3 January 2003

ENGLISH
Original: ENGLISH AND FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)

DRAFT SUPPLEMENT 5 TO REGULATION No. 87

(Daytime running lamps)

Note: The text reproduced below was adopted by the Administrative Committee (AC.1) of the amended 1958 Agreement at its twenty-second session, following the recommendation by WP.29 at its one-hundred-and-twenty-eighth session. It is based on document TRANS/WP.29/2002/59, not amended (TRANS/WP.29/885, para. 138).

Annex 3,

Add a new paragraph 4., to read:

"4. Photometric measurement of lamps

The photometric performance shall be checked:

4.1. For non-replaceable light sources (filament lamps or other):

with the light sources present in the lamp, in accordance with paragraph 10. of this Regulation.

4.2. For replaceable filament lamps:

when equipped with filament lamps at 6.75 V, 13.5 V or 28.0 V the luminous intensity values produced shall be corrected. The correction factor is the ratio between the reference luminous flux and the mean value of the luminous flux found at the voltage applied (6.75 V, 13.5 V or 28.0 V). The actual luminous fluxes of each filament lamp used shall not deviate more than " 5 per cent from the mean value. Alternatively a standard filament lamp may be used in turn, in each of the individual positions, operated at its reference flux, the individual measurements in each position being added together.

4.3. For any daytime running lamp except those equipped with filament lamp(s), the luminous intensities, measured after one minute and after 30 minutes of operation, shall comply with the minimum and maximum requirements. The luminous intensity distribution after one minute of operation can be calculated from the luminous intensity distribution after 30 minutes of operation by applying at each test point the ratio of luminous intensities measured at HV after one minute and after 30 minutes of operation."
