

29 August 2003

AGREEMENT

**CONCERNING THE ADOPTION OF UNIFORM TECHNICAL PRESCRIPTIONS
FOR WHEELED VEHICLES, EQUIPMENT AND PARTS WHICH CAN BE FITTED
AND/OR BE USED ON WHEELED VEHICLES AND THE CONDITIONS FOR
RECIPROCAL RECOGNITION OF APPROVALS GRANTED ON THE BASIS OF
THESE PRESCRIPTIONS */**

(Revision 2, including the amendments which entered into force on 16 October 1995)

Addendum 12: Regulation No. 13

Revision 4 - Amendment 2 - Corrigendum 2

Corrigendum 2 to Supplement 6 to the 09 series of amendments, subject of Depositary
Notification C.N.359.2003.TREATIES-1 dated 6 May 2003

**UNIFORM PROVISIONS CONCERNING THE APPROVAL OF VEHICLES OF
CATEGORIES M, N AND O WITH REGARD TO BRAKING**



UNITED NATIONS

*/ Former title of the Agreement:

Agreement Concerning the Adoption of Uniform Conditions of Approval and Reciprocal Recognition of Approval for Motor Vehicle Equipment and Parts, done at Geneva on 20 March 1958.

GE.03-23604

Annex 12,

Paragraphs 2.2.19.1. and 2.2.19.2., correct to read:

- "2.2.19.1. s_{Hz} : stroke of the master cylinder in millimetres according to figure 8 of appendix 1 to this annex;
- 2.2.19.2. s''_{Hz} : spare travel of the master cylinder in millimetres at piston rod, according to figure 8;"

Paragraph 2.2.22., correct to read:

- "2.2.22. $2s_B^*$ minimum brake shoe centre lift
-
- where: V_{60} = fluid volume absorbed by one wheel brake at a pressure

Paragraphs 2.2.23. and 2.2.23.1., correct to read:

- "2.2.23. M^* : Braking torque as specified by the manufacturer in paragraph 5. of appendix 3. This braking torque shall produce at least, the prescribed braking force B^* ;
- 2.2.23.1. M_T : Test braking torque in the case when no overload protector is fitted (according to paragraph 6.2.1. below);"

Paragraphs 2.2.26. and 2.2.27., correct to read:

- "2.2.26. M_r : Maximum braking torque resulting from the maximum permissible travel s_r or the maximum permissible fluid volume V_f when the trailer moves rearward (including rolling resistance = $0.01 \cdot g \cdot G_{Bo}$);
- 2.2.27. s_r : Maximum permissible travel at the brake control lever when the trailer moves rearward;"

Paragraph 2.2.28., correct to read:

- "2.2.28. V_r : Maximum permissible fluid volume absorbed by one braking wheel when the trailer moves rearward;"

Paragraphs 2.3.5. and 2.3.6., correct to read:

- "2.3.5. P: Force applied to the brake control lever; (see Figure 4 of appendix 1 to this annex);
- 2.3.6. P_o: Brake-retraction force when the trailer moves forward; i.e., in the graph of $M = f(P)$, the value of the force P at the point of intersection of the extrapolation of this function with the abscissa (see Figure 6 of appendix 1 to this annex);"

Paragraph 2.3.7., correct to read:

- "2.3.7. P*: Force applied to the brake control lever to produce the braking force B*;"

Paragraphs 2.3.9. and 2.3.9.1., correct to read:

- "2.3.9. ρ: characteristic of the brake when the trailer moves forward as defined from:

$$M = \rho (P - P_o)$$

- 2.3.9.1. ρ_r: characteristic of the brake when the trailer moves rearward as defined from:

$$M_r = \rho_r (P_r - P_{or})"$$

Paragraph 2.4.6., correct to read:

- "2.4.6. p_o: retraction pressure in the brake cylinder when the trailer moves forward; i.e., in graph of $M = f(p)$, the value of the pressure p at the point of intersection of the extrapolation of this function with the abscissa (see Figure 7 of appendix 1 to this annex);"

Paragraph 2.4.7., correct to read:

- "2.4.7. p*: Hydraulic pressure in the brake cylinder to produce the braking force B*;"

Paragraphs 2.4.9. and 2.4.9.1., correct to read:

- "2.4.9. ρ': characteristic of the brake when the trailer moves forward as defined from:

$$M = \rho' (p - p_o)$$

2.4.9.1. ρ'_T : characteristic of the brake when the trailer moves rearward as defined from:

$$M_T = \rho_T (p_r - p_{or})"$$

Paragraphs 2.5.1., correct to read:

"2.5.1. D_{op} : Application force at the input side of the control device, at which the overload protector is activated"

Paragraph 3.6., correct to read:

"3.6. Inertia braking systems may incorporate overload protectors. They must not be activated at a force of less than $D_{op} = 1.2 \cdot D^*$ (when fitted at the control device) or at a force of less than $P_{op} = 1.2 \cdot P^*$ or at a pressure of less than $p_{op} = 1.2 \cdot p^*$ (when fitted at the wheel brake) where the force P^* or the pressure p^* corresponds to a braking force of $B^* = 0,5 \cdot g \cdot G_{Bo}$."

Paragraphs 5.4.4. to 5.4.6., correct to read:

"5.4.4. surface area F_{HZ} of the piston in the master cylinder.

5.4.5. stroke s_{HZ} of the master cylinder (in millimetres).

5.4.6. spare travel s''_{HZ} of the master cylinder (in millimetres)."

Paragraph 6.1., correct to read:

"6.1. In addition to the brakes to be checked, the manufacturer shall submit to the Technical Service conducting the tests, drawings of the brakes showing the type, dimensions and material of the essential components and the make and type of the linings. In the case of hydraulic brakes, these drawings shall show the surface area F_{RZ} of the brake cylinders. The manufacturer shall also specify the braking torque M^* and the mass G_{Bo} defined in paragraph 2.2.4. of this annex."

Paragraph 6.2.1., correct to read:

"6.2.1. In the case when an overload protector is neither fitted nor intended to be fitted within the inertia (overrun) braking system, the wheel brake shall be tested with the following test forces or pressures:"

$$P_T = 1.8 P^* \text{ or } p_T = 1.8 p^* \text{ and } M_T = 1.8 M^* \text{ as appropriate.}"$$

Paragraphs 6.2.2.2. and 6.2.2.3., correct to read:

"6.2.2.2. The ranges of minimum test force P_{Top} or minimum test pressure p_{Top} and the minimum test torque M_{Top} are:

$$P_{Top} = 1.1 \text{ to } 1.2 P^* \text{ or } p_{Top} = 1.1 \text{ to } 1.2 p^* \quad \text{and}$$
$$M_{Top} = 1.1 \text{ to } 1.2 M^*$$

6.2.2.3. The maximum values (P_{op_max} or p_{op_max}) for the overload protector shall be specified by the manufacturer and shall not be more than P_T or p_T respectively."

Paragraph 7.3., correct to read:

"7.3. In the case of mechanical brakes, the following shall be determined:"

Paragraphs 7.3.2. and 7.3.3., correct to read:

"7.3.2. Force P^* for braking torque M^*

7.3.3. Torque M^* as a function of the force P^* applied to the control lever in mechanical-transmission systems. The rotational speed of the braking surfaces shall correspond to an initial vehicle speed of 60 km/h when the trailer moves forward and 6 km/h when the trailer moves rearward. The following shall be derived from the curve obtained from these measurements (see Figure 6 of appendix 1 to this annex):"

Paragraph 7.3.3.4., correct to read:

"7.3.3.4. Maximum permissible travel at the brake control lever when the trailer moves rearward (see Figure 6 of appendix 1 to this annex)"

Paragraphs 7.4.2. and 7.4.3., correct to read:

"7.4.2. Pressure p^* for braking torque M^*

7.4.3. Torque M^* as a function of the pressure p^* applied to the brake cylinder in hydraulic transmission systems. The rotational speed of the braking surfaces shall correspond to an initial vehicle speed of 60 km/h when the trailer moves forward and 6 km/h when the trailer moves rearward. The following shall be derived from the curve obtained from these measurements (see Figure 7 of appendix 1 to this annex):"

Paragraph 7.4.3.4., correct to read:

"7.4.3.4. Maximum permissible fluid volume V_f absorbed by one braking wheel when the trailer moves rearward (see figure 7 of appendix 1)."

Paragraph 7.4.4., correct to read:

"7.4.4. Surface area F_{RZ} of the piston in the brake cylinder."

Paragraphs 7.5. to 7.5.2., correct to read:

"7.5. Alternative Procedure for the Type-I test

7.5.1. The Type-I test according to annex 4, paragraph 1.5. does not have to be carried out on a vehicle submitted for type approval, if the braking system components are tested on an inertia test bench to meet the prescriptions of annex 4, paragraphs 1.5.2. and 1.5.3.

7.5.2. The alternative procedure for the Type-I test shall be carried out in accordance with the provisions laid down in annex 11, appendix 2, paragraph 3.5.2. (in analogy also applicable for disc brakes)."

Annex 12, appendix 2.

Item 8.2., correct to read:

"8.2. with hydraulic transmission device 1/

$i_h =$ from to 2/

$F_{HZ} =$ cm^2

travel of master cylinder s_{Hz} mm

spare travel of master cylinder s''_{Hz} mm"

Item 9.8.1.1., correct to read:

"9.8.1.1. Threshold force of the overload protector
 $D_{op} =$ N"

Items 9.8.1.2. and 9.8.1.3., correct to read:

"9.8.1.2. Where the overload protector is mechanical 1/
 max. force which the inertia control device can develop
 $P'_{max}/i_{Ho} = P_{op_max} = \dots\dots\dots N$

9.8.1.3. Where the overload protector is hydraulic 1/
 the pressure which the inertia control device can develop
 $p'_{max}/i_h = P_{op_max} = \dots\dots\dots N/cm^2$ "

Item 9.8.2.1., correct to read:

"9.8.2.1. Threshold force on the overload protector
 where the overload protector is mechanical 1/
 $D_{op_iHo} = \dots\dots\dots N$
 where the overload protector is hydraulic 1/
 $D_{op_ih} = \dots\dots\dots N$ "

Items 9.8.2.2. and 9.8.2.3., correct to read:

"9.8.2.2. Where the overload protector is mechanical 1/
 max force which the inertia control device can develop
 $P'_{max} = P_{op_max} = \dots\dots\dots N$

9.8.2.3. Where the overload protector is hydraulic 1/
 the pressure which the inertia control device can develop
 $p'_{max} = P_{op_max} = \dots\dots\dots N/cm^2$ "

Annex 12, appendix 3,

Items 9.6.1. and 9.6.1.A., correct to read:

"9.6.1. Braking torque activating the overload protector
 $M_{op} = \dots\dots\dots Nm$

9.6.1.A. Braking torque activating the overload protector
 $M_{op} = \dots\dots\dots Nm$ "

Items 9.10., 9.10.1. and 9.10.1A., correct to read:

"9.10. Service brake performance when the trailer moves rearwards (see figures 6 and 7 of
 appendix 1 to this annex)

9.10.1. Maximum Fig 6 braking torque $M_r = \dots\dots\dots Nm$

9.10.1.A. Maximum Fig 7 braking torque $M_r = \dots\dots\dots$ Nm"

Item 9.10.2.A., correct to read:

"9.10.2.A. Maximum permissible fluid volume absorbed $V_r = \dots\dots\dots$ cm³"

Item 9.11., correct to read:

"9.11. Further brake characteristics when the trailer moves rearwards (see figures 6 and 7 of appendix 1 to this annex)"

Item 9.12., correct to read:

"9.12. Tests according to paragraph 7.5. of this annex (if applicable)(corrected to take account of the rolling resistance corresponding to $0.01 \cdot g \cdot G_{Bo}$)"

Item 9.12.2., correct to read:

"9.12.2. Brake test Type I
Test speed = $\dots\dots\dots$ km/h

Sustained braking ratio = $\dots\dots\dots$ %

Braking time = $\dots\dots\dots$ minutes

Hot performance = $\dots\dots\dots$ %
(expressed as a % of the above Type-0 test result in item 9.12.1.)

Control force = $\dots\dots\dots$ N"

Annex 12, appendix 4,

Item 5.6., correct to read:

"5.6. Braking torque of the brakes
 $n \cdot M^* / (B \cdot R) = \dots\dots\dots$
(must be equal or greater than 1.0)"

Items 5.6.1.1. to 5.6.1.4., correct to read:

"5.6.1.1. where the overload protector is mechanical on the inertia control device 1/
 $n \cdot P^* / (i_{H1} \cdot \eta_{H1} \cdot P'_{max}) = \dots\dots\dots$
(must be equal or greater than 1.2)

5.6.1.2. where the overload protector is hydraulic on the inertia control device 1/
 $P^* / P'_{\max} = \dots\dots\dots$
(must be equal or greater than 1.2)

5.6.1.3. if the overload protector is on the inertia control device:
threshold force $D_{op}/D^* = \dots\dots\dots$
(must be equal or greater than 1.2)

5.6.1.4. if the overload protector is fitted on the brake:
threshold torque $n \cdot M_{op}/(B \cdot R) \dots\dots\dots$
(must be equal or greater than 1.2)"
