



**Economic and Social
Council**

Distr.
GENERAL

TRANS/WP.29/2005/14
22 December 2004

ENGLISH
Original: ENGLISH and FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations (WP.29)
(One-hundred-and-thirty-fifth session, 8-11 March 2005,
agenda item 4.2.11.)

PROPOSAL FOR DRAFT SUPPLEMENT 8 TO REGULATION No. 50

(Position, stop and direction indicator lamps for motorcycles)

Transmitted by the Working Party on Lighting and Light-Signalling (GRE)

Note : The text reproduced below was adopted by GRE at its fifty-third session and is transmitted for consideration to WP.29 and AC.1. It is based on document TRANS/WP.29/GRE/2004/26, not amended (TRANS/WP.29/GRE/53, para. 70).

This document is a working document circulated for discussion and comments. The use of this document for other purposes is the entire responsibility of the user.

Documents are also available via the INTERNET:

<http://www.unece.org/trans/main/welcwp29.htm>

Paragraphs 7.4.1., 7.4.1.1., 7.4.1.2. and 7.4.1.3., delete the reference to footnote 3/.

Footnote 3/, should be deleted.

Insert new paragraphs 7.11., 7.11.1. and 7.11.2., to read:

"7.11. Maximum values of front direction indicator lamps

7.11.1. For devices of categories 11 and 11a, the intensity of the the light emitted outside the zone defined by the measuring points ± 10 degrees H and ± 10 degrees V (10 degrees-field) shall not exceed the following values:

Direction indicator of category	Maximum values in cd outside the 10 degrees-field	
	Single lamp	Single lamp containing more than one light source
11	400	560
11a	400	560

Between the boundaries of the 10 degrees-field (± 10 degrees H and ± 10 degrees V) and the 5 degrees-field (± 5 degrees H and ± 5 degrees V), the maximum admissible values of the intensities are linearly increased up to the values as defined in paragraphs 7.4.1. and 7.4.1.1.;

7.11.2. For devices of categories 11b and 11c, the intensity of the light emitted outside the zone defined by the measuring points ± 15 degrees H and ± 15 degrees V (15 degrees-field) shall not exceed the following values:

Direction indicator of category	Maximum values in cd outside the 15 degrees-field	
	Single lamp	Single lamp containing more than one light source
11b	250	350
11c	400	560

Between the boundaries of the 15 degrees-field (± 15 degrees H and ± 15 degrees V) and the 5 degrees-field (± 5 degrees H and ± 5 degrees V), the maximum values are increased linearly up to the values as defined in paragraphs 7.4.1.2. and 7.4.1.3."