



**Economic and Social
Council**

Distr.
GENERAL

ECE/TRANS/WP.29/2010/40
18 December 2009

ENGLISH
Original: ENGLISH AND FRENCH

ECONOMIC COMMISSION FOR EUROPE

INLAND TRANSPORT COMMITTEE

World Forum for Harmonization of Vehicle Regulations

One-hundred-and-fiftieth session
Geneva, 9-12 March 2010
Item 4.2.36 of the provisional agenda

1958 AGREEMENT

Consideration of draft amendments to existing Regulations

Proposal for Supplement 6 to the 02 series of amendments to Regulation No. 107
(M₂ and M₃ vehicles)

Submitted by the Working Party on General Safety Provisions */

The text reproduced below was adopted by the Working Party on General Safety (GRSG) at its ninety-seventh session in order to clarify the dimensions of escape hatches in vehicles of Class B. It is based on ECE/TRANS/WP.29/GRSG/2009/13, as amended by the report (ECE/TRANS/WP.29/GRSG/76, para. 14). It is submitted to the World Forum for Harmonization of Vehicle Regulations (WP.29) and to the Administrative Committee (AC.1) for consideration.

*/ In accordance with the programme of work of the Inland Transport Committee for 2006-2010 (ECE/TRANS/166/Add.1, programme activity 02.4), the World Forum will develop, harmonize and update Regulations in order to enhance performance of vehicles. The present document is submitted in conformity with that mandate.

Insert new paragraphs 10.13. to 10.15., to read:

- "10.13. As from the official date of entry into force of the Supplement 6 to the 02 series of amendments, no Contracting Party applying this Regulation shall refuse to grant approval under this Regulation as amended by the Supplement 6 to the 02 series of amendments.
- 10.14. As from 12 months after the date of entry into force of the Supplement 6 to the 02 series of amendments, Contracting Parties applying this Regulation shall grant approvals only if the vehicle type to be approved meets the requirements of this Regulation as amended by Supplement 6 to the 02 series of amendments.
- 10.15. As from 30 months after the entry into force of Supplement 6 to the 02 series of amendments, Contracting Parties applying this Regulation may refuse to grant national/regional approvals and first national registration (first entry into service) of a vehicle which does not meet the requirements of Supplement 6 to the 02 series of amendments to this Regulation."

Annex 7, paragraph 1.1., amend to read:

"1.1. Minimum dimensions for exits

The several kinds of exits shall have the following minimum dimensions:

Aperture	Dimensions	Remarks
Service Door	<u>Entry height:</u> Class A 1,650 mm B 1,500 mm	The service door entry height shall be measured as the vertical distance measured on a vertical plane of the horizontal projections of the mid point of the door aperture and the top surface of the lowest step.
	Aperture Height	The vertical height of the service door aperture shall be such as to permit the free passage of the dual panel referred to in paragraph 7.7.1.1. of Annex 3. The upper corners may be reduced with round-offs, with a radius of not more than 150 mm.
	<u>Width:</u> Single door: 650 mm Double door: 1,200 mm	For Class B vehicles where the service door aperture height lies between 1,400 mm and 1,500 mm a minimum single door aperture width of 750 mm shall apply. For all the vehicles the width of any service door may be reduced by 100 mm when the measurement is made at the level of the handholds and by 250 mm in cases where intruding wheel arches or the actuating mechanism for automatic or remote-control doors or the rake of the windscreen so require.
Emergency door	Height: 1,250 mm Width: 550 mm	The width may be reduced to 300 mm in cases where intruding wheel arches so require, providing that the width of 550 mm is respected at the minimum height of 400 mm above the lowest part of the door aperture. The upper corners may be reduced with round-offs, with a radius of not more than 150 mm.
Emergency Window and Escape hatch	Aperture area: 400,000 mm ²	It shall be possible to inscribe in this area a rectangle of 500 mm x 700 mm.
